

# Smart Water Management System

1<sup>st</sup> Revati Mane

*School of Electronics and Telecommunication Engineering  
MIT Academy of Engineering Alandi, Pune  
Pune, Maharashtra*

2<sup>nd</sup> Sandhya Mane

*School of Electronics and Telecommunication Engineering  
MIT Academy of Engineering Alandi, Pune  
Pune, Maharashtra*

3<sup>rd</sup> Mr. Vaibhav Gijare

*School of Electronics and Telecommunication Engineering  
MIT Academy of Engineering Alandi, Pune  
Pune, Maharashtra*

4<sup>th</sup> Dr. Dipti Sakahre

*School of Electronics and Telecommunication Engineering  
MIT Academy of Engineering Alandi, Pune  
Pune, Maharashtra*

**Abstract**—The project "Water Level Monitoring Using ESP8266, Ultrasonic Sensor, and Blynk IoT" aims to create a smart water level monitoring system capable of real-time remote monitoring. This device measures water levels in tanks or reservoirs using an ultrasonic sensor (HC-SR04) coupled to an ESP8266 microprocessor. Data is transferred to the Blynk IoT platform, which allows clients to check water levels via a mobile app. The system is scalable, cost-effective, and offers precise and dependable monitoring for both residential and commercial applications. Future generations could include automated pump control, cloud data storage, and portable battery-powered operation.

## I. INTRODUCTION

For resource management in applications like irrigation, reservoirs, and water tanks, water level monitoring is crucial. This project measures water levels using an ESP8266 microcontroller and an ultrasonic sensor, sending data in real time to the Blynk IoT platform. By allowing users to remotely monitor and control water levels, the Blynk app increases water management efficiency. With the help of the system's precise, real-time data, users may minimise water waste, maximise resource use, and guarantee prompt replacement. The Blynk app is the perfect choice for both home and business applications because of its intuitive layout, which enables customisable alarms and historical data analysis. This economical and scalable solution supports wise resource management and sustainable water use. Furthermore, the seamless remote access and control from any location is made possible by the integration with IoT technology, guaranteeing dependability and ease. To give more thorough environmental data, the project can be further improved with more sensors, such as temperature and humidity sensors. This creative method encourages more intelligent decision-making, supporting sustainable development objectives and international water conservation initiatives. Because of its adaptability, the system can be used for a variety of purposes, such as flood disaster management, automated irrigation systems, and monitoring of municipal water supplies. Because of its low power consumption and low maintenance needs, it

is an environmentally beneficial solution that is likely to be widely adopted. The project may be extended to incorporate AI integration and predictive analytics for sophisticated water management techniques as technology develops, making it a solution that is prepared for the future.

## II. RELATED WORKS

Several research have tackled water level monitoring using various technologies:

- **Ultrasonic Technology for Water Level Monitoring:** Rural water supply management was shown to be effective with a reservoir water level measurement system built around the HC-SR04 ultrasonic sensor.
- **Internet of Things Monitoring:** In order to create scalable, reasonably priced water management solutions, researchers have combined ESP8266 microcontrollers with platforms such as Blynk.
- **Networks of Wireless Sensors (WSN):** Wireless sensor networks have been used to track river and dam water levels, sending data in real time to cloud servers for resource management and flood forecasting.
- **GSM-Based Surveillance:** Effective resource management was made possible by a water level monitoring system that used GSM modules to send users SMS notifications when water levels hit predetermined critical limits.
- **Smart Cloud-Based Systems:** For water level monitoring, systems that integrate cloud services like AWS IoT and Google Cloud have made data storage, visualisation, and historical analysis simple.
- **Predictive Monitoring with Machine Learning:** Based on past data, researchers have created machine learning-based algorithms that forecast patterns in water demand and streamline tank filling procedures.
- **Water Monitoring Solutions That Use Less Energy:** Research has looked on solar-powered low-power Internet of Things nodes that can operate dependably in isolated locations without access to traditional electricity.

### III. SYSTEM DESIGN

#### A. Components Used

TABLE I  
COMPONENTS AND SPECIFICATIONS

Component	Specification/Model	Quantity
ESP8266 (NodeMCU)	ESP-12E / NodeMCU	1
Ultrasonic Sensor	HC-SR04	1
Jumper Wires	Male-to-Male	5-6
Breadboard	Standard Size	1
USB Cable	Micro USB (for NodeMCU)	1

#### B. Working Principle

To determine the distance between itself and the water's surface, the HC-SR04 sensor sends out ultrasonic waves. After processing the data, the ESP8266 determines the water level by using the maximum depth of the tank. The gauge widget in the Blynk app allows users to view the data in real-time after it has been sent over Wi-Fi to the Blynk cloud.

#### C. System Architecture

The architecture of the smart water management system is illustrated in Fig. 1. The system includes a sensor, controller, wireless communication module, cloud integration, and user interface via mobile phone or PC.




Fig. 1. Block Diagram

### IV. METHODOLOGY

#### A. Hardware Configuration

The connections for the ultrasonic sensor are:

- **GND:** Ground.
- **TRIG:** Connected to GPIO 5 (D1) of ESP8266.
- **ECHO:** Connected to GPIO 4 (D2) of ESP8266.
- **VCC:** 5V power supply.

The water level is calculated using the formula:

$$\text{Time } (\mu\text{s}) \times 0.034$$

$$\text{Distance (cm)} = \frac{\text{Time } (\mu\text{s}) \times 0.034}{2} \quad (1)$$

The water level is then:

$$\text{Water Level (cm)} = \text{Maximum Tank Height (cm)} - \text{Distance (cm)} \quad (2)$$

#### B. Software Setup

- Install the Blynk app and create a project.
- Configure the Gauge Widget with Virtual Pin (V1) and range (e.g., 0–200 cm).
- Install the ESP8266 and Blynk libraries in the Arduino IDE.
- Connect NodeMCU to the PC via USB to upload the code.

#### C. Ease of Use

The smart water management system's component choices guarantee ease of use, accessibility, and integration. The Arduino IDE makes programming the ESP8266 NodeMCU simple, and it has built-in Wi-Fi for Internet of Things connectivity. The HC-SR04 ultrasonic sensor measures water level accurately and requires little setup. Prototyping without soldering is quick and effective thanks to a breadboard and jumper wires, which simplify circuit connections. Furthermore, the Blynk app provides an easy-to-use interface for displaying water level data on PCs or mobile devices, guaranteeing users' access in real time. Easy code uploading to the ESP8266 and a smooth power supply are made possible by the USB cable.

### V. OPERATION AND MAINTENANCE

#### A. Operation

The technology measures and transmits water level data in real time on its own. After being switched on, the ESP8266 determines the water level by reading data from the HC-SR04 ultrasonic sensor and uploading it to the Blynk cloud. The Blynk software allows users to keep an eye on their data on their PC or mobile device.

#### B. Maintenance

- Regularly inspect sensor connections to ensure they are clean and secure.
- Check the ultrasonic sensor for dust or water droplets on a regular basis.
- Keep an eye on Wi-Fi connectivity and make sure the network is always available.
- Check the power source to ensure continuous operation.
- When needed, update the firmware to get better performance.

### VI. FUTURE IMPROVEMENTS

- **Automated Pump Control:** Activates a pump based on predefined thresholds to maintain water levels automatically.
- **Alerts:** Users can receive real-time email or SMS notifications about critical water levels.
- **Cloud Data Storage:** Providing historical data storage for research, reporting, and improved water resource planning.
- **Battery Power Supply:** Use a battery-powered system for off-grid or remote operations.

- **Solar-Powered Operation:** Installing solar panels improves energy efficiency and enables deployment in rural or low-resource areas.
- **Multi-Tank Monitoring:** Using a network of sensors, the system is extended to monitor several tanks or reservoirs at once.
- **Machine Learning Integration:** Utilising predictive analytics to anticipate patterns in water usage and enhance resource management.
- **Leakage Detection:** Putting in sensors to find water supply leaks and stop water waste.
- **Voice Control Integration:** For improved use, voice commands can be integrated via Google Assistant or Amazon Alexa.
- **Mobile Dashboard Enhancements:** Improving the Blynk app's design to include visual insights like charts, graphs, and anomaly detection.

## VII. CONCLUSION

The suggested smart water management system offers an efficient, scalable, and cost-effective solution for real-time water level monitoring. The integration of the ESP8266 microcontroller, an ultrasonic sensor, and the Blynk IoT platform assures precision and convenience. This technology is suited for use in residential, agricultural, and industrial contexts and provides considerable benefits in water resource management. The system's capacity to deliver real-time data and customisable notifications enables users to manage possible concerns such as water overflow, shortages, and waste. Remote accessibility via the Blynk app improves user convenience by offering smooth monitoring and control from any place. Its modular architecture makes it simple to adapt and upgrade for new features, such as incorporating meteorological data or linking to smart irrigation systems. This smart water management system helps to conserve water and use resources more efficiently by encouraging sustainable practices and reducing water waste.

## ACKNOWLEDGEMENT

We would like to thank the MIT Academy of Engineering for providing the necessary resources and facilities to complete this research. We also thank our instructors and peers for their invaluable guidance.

## REFERENCES

- [1] Danilo De Freitas Melo, Epaminondas De Souza Lage, Anderson Vagner Rocha, "Improving the Consumption and Water Heating Efficiency in Smart Buildings," 2017.
- [2] Sangeeta Mandal, Somesh Kumar, Pinku Njani, "Smart IoT-Based Water Monitoring System Using Redundancy Elimination Strategy," 2021.
- [3] Abdoul Rjoub, Majed Alkhateeb, "ICT Smart Water Management System for Real-Time Applications," 2022.
- [4] V. Muthukumar, V. Selvakumar, M. Nalini, B. Chitradevi, "Cloud-Based Smart Water Management System," 2023.

